NOVRA GROUP

APPLICATIONS

Private Networks

- File-Based Video Broadcasting
- Digital Signage
- On-Demand Video
- Multi-Format File Server
- Video Streaming
- Internet Content Delivery
- Wireless LAN

FEATURES

- 2 1080P Displays Supported,
- Individual Content can be displayed
 on each monitor
- Web Browser Configuration and Diagnostics
- Deliver Content via IP
- Easy to deploy and control
 with Compel 2
- Field Upgradable Software
- Secure file delivery and reporting over internet using https://

Signcaster 815

Digital Media Player

The **Signcaster 815 Digital Media Player** provides high reliability, a small footprint and flexibility for enterprise business applications, such as client-facing digital signage, videoon-demand, employee training, serving data to 3rd party devices and aggregating data from multiple sources. It is designed to help display video, audio and data content in various controlled ways to end-users.

Use the Signcaster 815 Digital Media Player to:

- support HD and SD playlists
- display digital signage
- time-shift programming
- regionalize program insertions
- access media libraries (requires IR remote control kit)
- support internet file delivery
- access data files via LAN connection or WiFi

WEGENER's end-to-end solution includes network control components to maximize the distribution of live broadcasts, stored content and seamlessly re-use content for multiple media applications. It offers great flexibility for targeting content and remote configuration.



Compact form factor



TECHNICAL



ETHERNET INPUT		ENVIRON
IP Data	GigE*	Maximur
Connector	CAT5	Tempera
	Wireless WiFi	Dimensio
DATA FILES	VVII I	Power St
Storage	Std. HDD, Opt. SSD	UNIT CO
Access Modes	FTP, SMB, HTTP	Control
VIDEO CHARACTERISTICS		
Compression Codec	MPEG-1, MPEG-2, MPEG-4 AVC (H.264)	
Colour Sampling	4:2:0	PRODUC
Outputs	HDMI (2)	Access t
HD Resolution	720p, 1080p	and OSD
Display Support	Landscape(2)	Disk Stor
	Portrait (2)	Line Core
AUDIO CHARACTERISTIC	s	LAN IP S
Compression Codec	MPEG-1 Layer II	Protocol
		Format
Sample Rates	44.1 & 48 kHz	Codec
Optional Codecs	AAC, MP3, Dolby	Video Re
		Rate

ENVIRONMENTAL		
Maximum Operating Temperature	0-40 C (HDD) 1-50 C (SSD)	
Dimensions	4.5" x 4.5" x 2" (D x W x H)	
Power Supply	External 60W 19V power supply standard, 12V optional	
UNIT CONFIGURATION AND MONITORING		
Control	WEGENER Compel Control Local Web Interface On-screen display for LAN setup (requires IR remote control kit)	
PRODUCT OPTIONS		
Access to Media Library and OSD	IR Remote Control Kit	
Disk Storage Capacity	32 to 500 Gig Options	
Line Cord (Power Cord)	International	
LAN IP STREAM CHARACTERISTICS		
Protocol	UDP Multicast or TCP Unicast	
Format	Transport (Single Program)	
Codec	MPEG-2 and H.264 (Main, 4.1 Profile)	
Video Resolution	SD and HD	
Rate	Up to 10 Mbps	
Multicast	or 5 Mbps Unicast	

* Jumbo packets not supported

Product specifications are subject to change without notice



Wegener Corporation • www.wegener.com • +1 770.814.4000 Datasheet Version 1. May 2022